จิจช**ว**89 25X1

## CENTRAL INTELLIGENCE AGENCY

## INFORMATION REPORT

This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

COUNTRY	Czechoslovakia	REPORT
SUBJECT	Welding Machine Froduced at the Chotebor Metal Works, Chotebor	DATE DISTR. 5 October 1954
		NO. OF PAGES 3
DATE OF INFO.		REQUIREMENT NO. RD
PLACE ACQUIRED		REFERENCES
	This is UNEVALUATED	

SECRET/U.S. OFFICIALS ONLY

THE SOURCE EVALUATIONS IN THIS REPORT ARE DEFINITIVE.

THE APPRAISAL OF CONTENT IS TENTATIVE.

(FOR KEY SEE REVERSE)

- 1. A new welding machine, made at the Chotebor Works, was sused for the first time in July 1953 at the Kralovo Pole Plant of the Gottwald Works in Brno-Kralovo Fole to replace hand-operated electric welding machines.
- 2. The mechanism with the motor is in an aluminum case, 300 x 150 x 600 mm. in size (see No. 1 on diagram). The power inlet is in the front of the case (No. 2). The case is on four wheels. On top of the case is a drum on which the welding wire (electrode) is wound (No. 3). A ribbed cooling apparatus to prevent everheating of the motor is on top of the case (No. 4). Behind 25X1 it is the support to prevent sagging of the wire (No. 5). A regulator controlling the movements of the drum and of the cooling apparatus is on the edge, below the support (No. 6). The motor-speed-regulating button as well as the electric switch are on top (Nos. 7 and 8). The switch is connected with the welding apparatus, and when the motor is switched on, the welding machine is also put into operation. The electrode enters the actual welding holder attached to the front part (No. 9). This holder can be adjusted to required height and positions. It opens into a funnel into which the welding mixture is inserted.
- 3. This machine is based on the electric-arc-welding principle. It has a protecting device which prevents radiation and is therefore not as dangerous as the hand-operated welding machine.
- 4. It is suitable for welding steel sheets of major length and thicknesses of from 10 to 40 mms. The welded parts are smooth and further machining is necessary.


SECRET/U.S. OFFICIALS ONLY


STATE	x	ARMY	_ x	NAVY	х	AIR	X	FBI	П	AEC		ORR EV X
i											<u> </u>	
L												i

<b>⇔</b>	Y		
₹.	SECRET/	U.S. OFFICIALS ONLY	25X1
		- 2 -	
	Comments: ·		25X1
1951-52 Enterpr: 2. Now 1 Machine	as the Chotebor Metal 1 ise, in Chotebor. known as the Brno-Kralo	plant listed in the Pardubice te Works (Choteborske kovodelne zavo vo Pole Plant of the First Brno a (Prvni brnenska a kralovopolska s	dỳ), National nd Kralovo Pole
			25 <b>X</b> 1

Approved For Release 2007/09/24 : CIA-RDP80-00810A004700640004-9

SECRET/U.S. OFFICIALS ONLY





- 1. Mechanism inside the aluminum case.
- 2. Power inlet.
- 3. Drum of the welding wire.
- 4. Cooling apparatus.
- 5. Support of the welding wire.
  6. Regulator for turning the drum and the cooling apparatus.
- 7. Speed-control button.
- 8. Electric switch.
- 9. Funnel for welding mixture.
- 10. Welding wire.
- Welding holder.
   Device for adjustment of height and position of the holder.

SECRET/U.S. OFFICIALS ONLY